



ENERGY STAR® Program Requirements Product Specification for Computer Servers

Eligibility Criteria Final Draft Version 2.0

1 Following is the Version 2.0 ENERGY STAR Product Specification for Computer Servers. A product shall
2 meet all of the identified criteria if it is to earn the ENERGY STAR.

3 **1 DEFINITIONS**

4 A) Product Types:

- 5 1) Computer Server: A computer that provides services and manages networked resources for
6 client devices (e.g., desktop computers, notebook computers, thin clients, wireless devices,
7 PDAs, IP telephones, other computer servers, or other network devices). A computer server
8 is sold through enterprise channels for use in data centers and office/corporate environments.
9 A computer server is primarily accessed via network connections, versus directly-connected
10 user input devices such as a keyboard or mouse. For purposes of this specification, a
11 computer server must meet **all** of the following criteria:
- 12 a) is marketed and sold as a Computer Server;
 - 13 b) is designed for and listed as supporting one or more computer server operating systems
14 (OS) and/or hypervisors;
 - 15 c) is targeted to run user-installed applications typically, but not exclusively, enterprise in
16 nature;
 - 17 d) provides support for error-correcting code (ECC) and/or buffered memory (including both
18 buffered dual in-line memory modules (DIMMs) and buffered on board (BOB)
19 configurations).
 - 20 e) is packaged and sold with one or more ac-dc or dc-dc power supplies; and
 - 21 f) is designed such that all processors have access to shared system memory and are
22 visible to a single OS or hypervisor.
- 23 2) Managed Server: A computer server that is designed for a high level of availability in a highly
24 managed environment. For purposes of this specification, a managed server must meet **all** of
25 the following criteria:
- 26 a) is designed to be configured with redundant power supplies; and
 - 27 b) contains an installed dedicated management controller (e.g., service processor).
- 28 3) Blade System: A system comprised of a blade chassis and one or more removable blade
29 servers and/or other units (e.g., blade storage, blade network equipment). Blade systems
30 provide a scalable means for combining multiple blade server or storage units in a single
31 enclosure, and are designed to allow service technicians to easily add or replace (hot-swap)
32 blades in the field.
- 33 a) Blade Server: A computer server that is designed for use in a blade chassis. A blade
34 server is a high-density device that functions as an independent computer server and
35 includes at least one processor and system memory, but is dependent upon shared blade
36 chassis resources (e.g., power supplies, cooling) for operation. A processor or memory
37 module that is intended to scale up a standalone server is not considered a Blade Server.
- 38 (1) *Multi-bay Blade Server:* A blade server requiring more than one bay for installation in

- 39 a blade chassis.
- 40 (2) *Single-wide Blade Server*: A blade server requiring the width of a standard blade
41 server bay.
- 42 (3) *Double-wide Blade Server*: A blade server requiring twice the width of a standard
43 blade server bay.
- 44 (4) *Half-height Blade Server*: A blade server requiring one half the height of a standard
45 blade server bay.
- 46 (5) *Quarter-height Blade Server*: A blade server requiring one quarter the height of a
47 standard server bay.
- 48 b) Blade Chassis: An enclosure that contains shared resources for the operation of blade
49 servers, blade storage, and other blade form-factor devices. Shared resources provided
50 by a chassis may include power supplies, data storage, and hardware for dc power
51 distribution, thermal management, system management, and network services.
- 52 c) Blade Storage: A storage device that is designed for use in a blade chassis. A blade
53 storage device is dependent upon shared blade chassis resources (e.g., power supplies,
54 cooling) for operation.
- 55 4) Fully Fault Tolerant Server: A computer server that is designed with complete hardware
56 redundancy, in which every computing component is replicated between two nodes running
57 identical and concurrent workloads (i.e., if one node fails or needs repair, the second node
58 can run the workload alone to avoid downtime). A fully fault tolerant server uses two systems
59 to simultaneously and repetitively run a single workload for continuous availability in a
60 mission critical application.
- 61 5) Resilient Server: A computer server designed with extensive Reliability, Availability,
62 Serviceability (RAS) and scalability features integrated in the micro architecture of the
63 system, CPU and chipset. For purposes of ENERGY STAR qualification under this
64 specification, a Resilient Server shall have the characteristics as described in Appendix B of
65 this specification.
- 66 6) Multi-node Server: A computer server that is designed with two or more independent server
67 nodes that share a single enclosure and one or more power supplies. In a multi-node server,
68 power is distributed to all nodes through shared power supplies. Server nodes in a multi-node
69 server are not designed to be hot-swappable.
- 70 a) Dual-node Server: A common multi-node server configuration consisting of two server
71 nodes.
- 72 7) Server Appliance: A computer server that is bundled with a pre-installed operating system
73 and application software that is used to perform a dedicated function or set of tightly coupled
74 functions. Server appliances deliver services through one or more networks (e.g., IP or SAN),
75 and are typically managed through a web or command line interface. Server appliance
76 hardware and software configurations are customized by the vendor to perform a specific
77 task (e.g., name services, firewall services, authentication services, encryption services, and
78 voice-over-IP (VoIP) services), and are not intended to execute user-supplied software.
- 79 8) High Performance Computing (HPC) System: A computing system which is designed and
80 optimized to execute highly parallel applications. HPC systems feature a large number of
81 clustered homogeneous nodes often featuring high speed inter-processing interconnects as
82 well as large memory capability and bandwidth. HPC systems may be purposely built, or
83 assembled from more commonly available computer servers. HPC systems must meet ALL
84 the following criteria:
- 85 a) Marketed and sold as a Computer Server optimized for higher performance computing
86 applications;
- 87 b) Designed (or assembled) and optimized to execute highly parallel applications;

- 88 c) Consist of a number of typically homogeneous computing nodes, clustered primarily to
89 increase computational capability;
- 90 d) Includes high speed IPC interconnections between nodes.

91 **Note:** Based on stakeholder feedback, EPA has revised the language in requirement 8a above to provide
92 a clearer distinction between high performance computing and high performance computers.

93 9) Direct Current (Dc) Server: A computer server that is designed solely to operate on a dc
94 power source.

95 10) Large Server: A resilient/scalable server which ships as a pre-integrated/pre-tested system
96 housed in one or more full frames or racks and that includes a high connectivity I/O
97 subsystem with a minimum of 32 dedicated I/O slots.

98 B) Product Category: A second-order classification or sub-type within a product type that is based on
99 product features and installed components. Product categories are used in this specification to
100 determine qualification and test requirements.

101 C) Computer Server Form Factors:

102 1) Rack-mounted Server: A computer server that is designed for deployment in a standard 19-
103 inch data center rack as defined by EIA-310, IEC 60297, or DIN 41494. For the purposes of
104 this specification, a blade server is considered under a separate category and excluded from
105 the rack-mounted category.

106 2) Pedestal Server: A self-contained computer server that is designed with PSUs, cooling, I/O
107 devices, and other resources necessary for stand-alone operation. The frame of a pedestal
108 server is similar to that of a tower client computer.

109 D) Computer Server Components:

110 1) Power Supply Unit (PSU): A device that converts ac or dc input power to one or more dc
111 power outputs for the purpose of powering a computer server. A computer server PSU must
112 be self-contained and physically separable from the motherboard and must connect to the
113 system via a removable or hard-wired electrical connection.

114 a) Ac-Dc Power Supply: A PSU that converts line-voltage ac input power into one or more
115 dc power outputs for the purpose of powering a computer server.

116 b) Dc-Dc Power Supply: A PSU that converts line-voltage dc input power to one or more dc
117 outputs for the purpose of powering a computer server. For purposes of this specification,
118 a dc-dc converter (also known as a voltage regulator) that is internal to a computer server
119 and is used to convert a low voltage dc (e.g., 12 V dc) into other dc power outputs for use
120 by computer server components is not considered a dc-dc power supply.

121 c) Single-output Power Supply: A PSU that is designed to deliver the majority of its rated
122 output power to one primary dc output for the purpose of powering a computer server.
123 Single-output PSUs may offer one or more standby outputs that remain active whenever
124 connected to an input power source. For purposes of this specification, the total rated
125 power output from any additional PSU outputs that are not primary and standby outputs
126 shall be no greater than 20 watts. PSUs that offer multiple outputs at the same voltage as
127 the primary output are considered single-output PSUs unless those outputs (1) are
128 generated from separate converters or have separate output rectification stages, or (2)
129 have independent current limits.

130 d) Multi-output Power Supply: A PSU that is designed to deliver the majority of its rated
131 output power to more than one primary dc output for the purpose of powering a computer
132 server. Multi-output PSUs may offer one or more standby outputs that remain active
133 whenever connected to an input power source. For purposes of this specification, the
134 total rated power output from any additional PSU outputs that are not primary and
135 standby outputs is greater than or equal to 20 watts.

- 136
137
138
139
140
- 2) I/O Device: A device which provides data input and output capability between a computer server and other devices. An I/O device may be integral to the computer server motherboard or may be connected to the motherboard via though expansion slots (e.g., PCI, PCIe). Examples of I/O devices include discrete Ethernet devices, InfiniBand devices, RAID/SAS controllers, and Fibre Channel devices.
- 141
142
143
- a) I/O Port: Physical circuitry within an I/O device where an independent I/O session can be established. A port is not the same as a connector receptacle; it is possible that a single connector receptacle can service multiple ports of the same interface.
- 144
145
146
- 3) Motherboard: The main circuit board of the server. For purposes of this specification, the motherboard includes connectors for attaching additional boards and typically includes the following components: processor, memory, BIOS, and expansion slots.
- 147
148
149
150
151
- 4) Processor: The logic circuitry that responds to and processes the basic instructions that drive a server. For purposes of this specification, the processor is the central processing unit (CPU) of the computer server. A typical CPU is a physical package to be installed on the server motherboard via a socket or direct solder attachment. The CPU package may include one or more processor cores.
- 152
153
- 5) Memory: For purposes of this specification, memory is a part of a server external to the processor in which information is stored for immediate use by the processor.
- 154
155
- 6) Hard Drive (HDD): The primary computer storage device which reads and writes to one or more rotating magnetic disk platters.
- 156
157
- 7) Solid State Drive (SSD): A storage device that uses memory chips instead of rotating magnetic platters for data storage.

158 E) Other Datacenter Equipment:

- 159
160
161
162
- 1) Network Equipment: A device whose primary function is to pass data among various network interfaces, providing data connectivity among connected devices (e.g., routers and switches). Data connectivity is achieved via the routing of data packets encapsulated according to Internet Protocol, Fibre Channel, InfiniBand or similar protocol.
- 163
164
165
166
167
168
169
170
171
172
173
- 2) Storage Product: A fully-functional storage system that supplies data storage services to clients and devices attached directly or through a network. Components and subsystems that are an integral part of the storage product architecture (e.g., too provide internal communications between controllers and disks) are considered to be part of the storage product. In contrast, components that are normally associated with a storage environment at the data center level (e.g., devices required for operation of an external SAN) are not considered to be part of the storage product. A storage product may be composed of integrated storage controllers, storage devices, embedded network elements, software, and other devices. While storage products may contain one or more embedded processor, these processors do not execute user-supplied software applications but may execute data-specific applications (e.g., data replication, backup utilities, data compression, install agents).
- 174
175
176
- 3) Uninterruptible Power Supply (UPS): Combination of convertors, switches, and energy storage devices (such as batteries) constituting a power system for maintaining continuity of load power in case of input power failure.

177 F) Operational Modes and Power States:

- 178
179
180
181
182
- 1) Idle State: The operational state in which the OS and other software have completed loading, the computer server is capable of completing workload transactions, but no active workload transactions are requested or pending by the system (i.e., the computer server is operational, but not performing any useful work). For systems where ACPI standards are applicable, Idle State correlates only to ACPI System Level S0.
- 183
184
- 2) Active State: The operational state in which the computer server is carrying out work in response to prior or concurrent external requests (e.g., instruction over the network). Active

185 state includes **both** (1) active processing and (2) data seeking/retrieval from memory, cache,
186 or internal/external storage while awaiting further input over the network.

187 G) Other Key Terms:

- 188 1) Controller System: A computer or computer server that manages a benchmark evaluation
189 process. The controller system performs the following functions:
- 190 a) start and stop each segment (phase) of the performance benchmark;
 - 191 b) control the workload demands of the performance benchmark;
 - 192 c) start and stop data collection from the power analyzer so that power and performance
193 data from each phase can be correlated;
 - 194 d) store log files containing benchmark power and performance information;
 - 195 e) convert raw data into a suitable format for benchmark reporting, submission and
196 validation; and
 - 197 f) collect and store environmental data, if automated for the benchmark.
- 198 2) Network Client (Testing): A computer or computer server that generates workload traffic for
199 transmission to a UUT connected via a network switch.
- 200 3) RAS Features: An acronym for reliability, availability, and serviceability features. RAS is
201 sometimes expanded to RASM, which adds “Manageability” criteria. The three primary
202 components of RAS as related to a computer server are defined as follows:
- 203 a) *Reliability Features*: Features that support a server’s ability to perform its intended
204 function without interruption due to component failures (e.g., component selection,
205 temperature and/or voltage de-rating, error detection and correction).
 - 206 b) *Availability Features*: Features that support a server’s ability to maximize operation at
207 normal capacity for a given duration of downtime (e.g., redundancy [both at micro- and
208 macro-level]).
 - 209 c) *Serviceability Features*: Features that support a server’s ability to be serviced without
210 interrupting operation of the server (e.g., hot plugging).
- 211 4) Server Processor Utilization: The ratio of processor computing activity to full-load processor
212 computing activity at a specified voltage and frequency, measured instantaneously or with a
213 short term average of use over a set of active and/or idle cycles.
- 214 5) Hypervisor: A type of hardware virtualization technique that enables multiple guest operating
215 systems to run on a single host system at the same time.
- 216 6) Auxiliary Processing Accelerators (APAs): Computing expansion add-in cards installed in
217 general-purpose add-in expansion slots (e.g., GPGPUs installed in a PCI slot).
- 218 7) Buffered DDR Channel: Channel or Memory Port connecting a Memory Controller to a
219 defined number of memory devices (e.g. DIMMs) in a computer server. A typical computer
220 server may contain multiple Memory Controllers, which may in turn support one or more
221 Buffered DDR Channels. As such, each Buffered DDR Channel serves only a fraction of the
222 total addressable memory space in a computer server.

223 **Note:** EPA has moved the APA definition from Section 3.9, as presented in Draft 3, to Section 1:
224 Definitions in this Final Draft so that reviewers are able to locate all definitions in the same place.
225 EPA has also added the Buffered DDR Channel definition (item G7). The DDR Channel is discussed later
226 in this document in relation to the proposed Buffered DDR Channel adder for Resilient Servers in Table 4.

- 227 H) Product Family: A high-level description referring to a group of computers sharing one
228 chassis/motherboard combination that often contains hundreds of possible hardware and software
229 configurations.

- 230 1) Common Product Family Attributes: A set of features common to all models/configurations
231 within a product family that constitute a common basic design. All models/configurations
232 within a product family must share the following:
- 233 a) Be from the same model line or machine type;
 - 234 b) Share the same form factor (i.e., rack-mounted, blade, pedestal);
 - 235 c) Either share processors from a single defined processor series or share processors that
236 plug into a common socket type.

237 **Note:** As noted in Draft 3, fully populated and partially populated configurations are considered to be in
238 the same family; however, ENERGY STAR certifications will be based on measurements taken with fully
239 populated sockets (as allowed by the architecture). As an example: In the case of two socket servers two
240 processor configurations shall be used for certification purposes, but the system can be sold with one
241 processor under the same family without additional testing.

- 242 d) Share PSUs that perform with efficiencies greater than or equal to the efficiencies at all
243 required load points specified in Section 3.2 (i.e., 10%, 20%, 50%, and 100% of
244 maximum rated load for single-output; 20%, 50%, and 100% of maximum rated load for
245 multi-output).
- 246 2) Product Family Tested Product Configurations:
- 247 a) Purchase Consideration Variations:
 - 248 (1) Low-end Performance Configuration: The combination of Processor Socket Power,
249 PSUs, Memory, Storage (HDD/SDD), and I/O devices that represents the lower-price
250 or lower-performance computing platform within the Product Family.
 - 251 (2) High-end Performance Configuration: The combination of Processor Socket Power,
252 PSUs, Memory, Storage (HDD/SDD), and I/O devices that represents either the
253 higher-price or higher-performance computing platform within the Product Family.
 - 254 b) Typical Configuration:
 - 255 (1) Typical Configuration: A product configuration that lies between the Minimum and
256 Maximum Power configurations and is representative of a deployed product with high
257 volume sales.
 - 258 c) Power Utilization Variations:
 - 259 (1) Minimum Power Configuration: The minimum configuration that is able to boot and
260 execute supported OSs. The Minimum Configuration contains the lowest Processor
261 Socket Power, least number of installed PSUs, Memory, Storage (HDD/SDD), and
262 I/O devices, that is both offered for sale and capable of meeting ENERGY STAR
263 requirements.
 - 264 (2) Maximum Power Configuration: The vendor-selected combination of components that
265 maximize power usage within the Product Family once assembled and operated. The
266 Maximum Configuration contains the highest Processor Socket Power, greatest
267 number of installed PSUs, Memory, Storage (HDD/SDD), and I/O devices that is both
268 offered for sale and capable of meeting ENERGY STAR requirements.

269
270

271 2 SCOPE

272 2.1 Included Products

273 2.1.1 A product must meet the definition of a Computer Server provided in *Section 1* of this document
274 to be eligible for ENERGY STAR qualification under this specification. Eligibility under Version 2.0
275 is limited to Blade-, Multi-node, Rack-mounted, or Pedestal form factor computer servers with no
276 more than four processor sockets in the computer server (or per blade or node in the case of
277 blade or multi-node servers) Products explicitly excluded from Version 2.0 are identified in
278 *Section 2.2*.

279 2.2 Excluded Products

280 2.2.1 Products that are covered under other ENERGY STAR product specifications are not eligible for
281 qualification under this specification. The list of specifications currently in effect can be found at
282 www.energystar.gov/products.

283 2.2.2 The following products are not eligible for qualification under this specification:

- 284 i. Fully Fault Tolerant Servers;
- 285 ii. Server Appliances;
- 286 iii. High Performance Computing Systems;
- 287 iv. Large Servers;
- 288 v. Storage Products including Blade Storage; and
- 289 vi. Network Equipment.

290 3 QUALIFICATION CRITERIA

291 3.1 Significant Digits and Rounding

292 3.1.1 All calculations shall be carried out with directly measured (unrounded) values.

293 3.1.2 Unless otherwise specified, compliance with specification limits shall be evaluated using directly
294 measured or calculated values without any benefit from rounding.

295 3.1.3 Directly measured or calculated values that are submitted for reporting on the ENERGY STAR
296 website shall be rounded to the nearest significant digit as expressed in the corresponding
297 specification limit.

298 3.2 Power Supply Requirements

299 3.2.1 Power supply test data and test reports from testing entities recognized by EPA to perform power
300 supply testing shall be accepted for the purpose of qualifying the ENERGY STAR product.

301 3.2.2 Power Supply Efficiency Criteria: Power Supplies used in products eligible under this specification
302 must meet the following requirements when tested using the *Generalized Internal Power Supply*
303 *Efficiency Test Protocol, Rev. 6.6* (available at www.efficientpowersupplies.org). Power Supply
304 data generated using Rev. 6.4.2 (as required in Version 1.1), 6.4.3, or 6.5 are acceptable
305 provided the test was conducted prior to the effective date of Version 2.0 of this specification.

- 306 i. Pedestal and Rack-mounted Servers: To qualify for ENERGY STAR, a pedestal or rack-
307 mounted computer server must be configured with **only** PSUs that meet or exceed the
308 applicable efficiency requirements specified in Table 1 **prior to shipment**.

- 309 ii. Blade and Multi-node Servers: To qualify for ENERGY STAR, a Blade or Multi-node
 310 computer server shipped with a chassis must be configured such that **all** PSUs supplying
 311 power to the chassis meet or exceed the applicable efficiency requirements specified in Table
 312 **1 prior to shipment**.

313 **Table 1: Efficiency Requirements for PSUs**

Power Supply Type	Rated Output Power	10% Load	20% Load	50% Load	100% Load
Multi-output (Ac-Dc)	All Output Levels	N/A	85%	88%	85%
Single-output (Ac-Dc)	All Output Levels	80%	88%	92%	88%

314 3.2.3 Power Supply Power Factor Criteria: Power Supplies used in Computers eligible under this
 315 specification must meet the following requirements when tested using the *Generalized Internal*
 316 *Power Supply Efficiency Test Protocol, Rev. 6.6* (available at www.efficientpowersupplies.org).
 317 Power Supply data generated using Rev. 6.4.2 (as required in Version 1.1), 6.4.3, or 6.5 are
 318 acceptable provided the test was conducted prior to the effective date of Version 2.0.

- 319 i. Pedestal and Rack-mounted Servers: To qualify for ENERGY STAR, a pedestal or rack-
 320 mounted computer server must be configured with **only** PSUs that meet or exceed the
 321 applicable power factor requirements specified in Table 2 **prior to shipment**, under all
 322 loading conditions for which output power is greater than or equal to 75 watts. Partners are
 323 required to measure and report PSU power factor under loading conditions of less than 75
 324 watts, though no minimum power factor requirements apply.
- 325 ii. Blade or Multi-node Servers: To qualify for ENERGY STAR, a Blade or Multi-node computer
 326 server shipped with a chassis must be configured such that **all** PSUs supplying power to the
 327 chassis meet or exceed the applicable power factor requirements specified in Table 2 **prior**
 328 **to shipment**, under all loading conditions for which output power is greater than or equal to
 329 75 watts. Partners are required to measure and report PSU power factor under loading
 330 conditions of less than 75 watts, though no minimum power factor requirements apply.

331 **Table 2: Power Factor Requirements for PSUs**

Power Supply Type	Rated Output Power	10% Load	20% Load	50% Load	100% Load
Ac-Dc Multi-output	All Output Ratings	N/A	0.80	0.90	0.95
Ac-Dc Single-output	Output Rating ≤ 500 W	N/A	0.80	0.90	0.95
	Output Rating > 500 W and Output Rating ≤ 1,000 W	0.65	0.80	0.90	0.95
	Output Rating > 1,000 watts	0.80	0.90	0.90	0.95

332

333 **Note:** EPA has removed Dc-Dc requirements from Table 1 and Table 2 above as there is currently no
 334 procedure to test dc servers in the Version 2.0 Computer Servers Test Method. EPA and DOE will revisit
 335 including Dc-Dc computer servers in the Version 3.0 specification revision process.

336 **3.3 Power Management Requirements**

337 3.3.1 Server Processor Power Management: To qualify for ENERGY STAR, a Computer Server must
338 offer processor power management that is enabled by default in the BIOS and/or through a
339 management controller, service processor, and / or the operating system shipped with the
340 computer server. **All** processors must be able to reduce power consumption in times of low
341 utilization by

342 i. reducing voltage and/or frequency through Dynamic Voltage and Frequency Scaling (DVFS),
343 or

344 ii. enabling processor or core reduced power states when a core or socket is not in use.

345 3.3.2 Supervisor Power Management: To qualify for ENERGY STAR, a product which offers a pre-
346 installed supervisor system (e.g., operating system, hypervisor) must offer supervisor system
347 power management that is enabled by default.

348 3.3.3 Power Management Disclosure: To qualify for ENERGY STAR, all power management
349 techniques that are enabled by default must be itemized on the Power and Performance Data
350 Sheet. This requirement applies to power management features in the BIOS, operating system,
351 or any other origin that can be configured by the end-user.

352 **3.4 Blade and Multi-Node System Criteria**

353 3.4.1 Blade and Multi-Node Thermal Management and Monitoring: To qualify for ENERGY STAR, a
354 blade or multi-node server must provide real-time chassis or blade/node inlet temperature
355 monitoring and fan speed management capability that is enabled by default.

356 3.4.2 Blade and Multi-Node Server Shipping Documentation: To qualify for ENERGY STAR, a blade or
357 multi-node server that is shipped to a customer independent of the chassis must be accompanied
358 with documentation to inform the customer that the blade or multi-node server is ENERGY STAR
359 qualified only if it is installed in a chassis meeting requirements in *Section 3.4.1* of this document.
360 A list of qualifying chassis and ordering information must also be provided as part of product
361 collateral provided with the blade or multi-node server. These requirements may be met via either
362 printed materials, electronic documentation provided with the blade or multi-node server, or
363 information publically available on the Partner's website where information about the blade or
364 multi-node server is found.

365 **Note:** In response to stakeholder comments, EPA has revised Section 3.4 to clarify the documentation
366 requirements applicable to multi-node servers. Multi-node servers are subject to the same qualification
367 criteria as blade servers. Testing criteria have been added in Section 3.9 below.

368 **3.5 Active State Efficiency Criteria**

369 3.5.1 Active Mode Efficiency Disclosure: To qualify for ENERGY STAR, a Computer Server or
370 Computer Server Product Family must be submitted for qualification with the following information
371 disclosed in full and in the context of the complete active mode efficiency rating test report:

372 i. Final SERT rating tool results, which include the results files (both html and text format) and
373 all results-chart png files; and

374 ii. Intermediate SERT rating tool results over the entire test run, which include the results-details
375 files (both html and text format) and all results-details-chart png files.

376 Public disclosure and formatting requirements are discussed in *Section 4.1* of this specification.

377 3.5.2 Incomplete Disclosure: Partners shall not selectively report individual workload module results, or
378 otherwise present efficiency rating tool results in any form other than a complete test report, in
379 customer documentation or marketing materials.

380

381
382
383
384
385
386

Note: EPA has decided that there will be a 9 month period of time after Version 2.0 is published in which the SERT data submitted to EPA will be published anonymously. This will provide a window for EPA and stakeholders to evaluate SERT results before presenting them to the consumer at the effective date. At 9 months, all SERT test data for ENERGY STAR certified Servers will be made public and attached to the particular products or product families which generated the results, as is the case with all other ENERGY STAR certified products.

387
388

3.6 Idle State Efficiency Criteria – One-Socket (1S) and Two-Socket (2S) Servers (neither Blade nor Multi-Node)

389
390

3.6.1 Idle State Efficiency: Measured Idle State power (P_{IDLE}) shall be less than or equal to the Maximum Idle State Power Requirement (P_{IDLE_MAX}), as calculated per Equation 1.

391

Equation 1: Calculation of Maximum Idle State Power

392

$$P_{IDLE_MAX} = P_{BASE} + \sum_{i=1}^n P_{ADDL_i}$$

393
394
395
396
397
398
399

Where:

- P_{IDLE_MAX} is the Maximum Idle State Power Requirement,
- P_{BASE} is the base idle power allowance, as determined per Table 3,
- P_{ADDL_i} is the Idle State power allowance for additional components, as determined per Table 4.

400
401
402

- i. These Idle power limits are applicable to one and two socket systems only.
- ii. Use Section 6.1 of the ENERGY STAR Computer Servers Test Method to determine the Idle State power for qualification.

403
404
405
406
407
408

Note: Stakeholders have raised concerns about the potential impact on idle state measurement values when idle is measured in a “cold” system prior to exposure to heavy workloads versus when tested in a “warm” system where the fan power consumption may be higher. To minimize the impact this change may have on data used for certification, EPA is requiring that idle state data used for certification purposes continues to be measured using the manual idle measurement procedures as defined in Section 6.1 of the ENERGY STAR Computer Servers Test Method Draft Final (Rev. Jan-2013).

409
410
411
412
413
414
415
416
417
418
419
420
421
422
423

- iii. The Resilient category in Table 3 applies only to two socket systems that meet the definition of Resilient Server as set forth in Appendix B.
- iv. All quantities (with the exception of installed processors) in Table 3 and Table 4 refer to the number of components installed in the system, not the maximum number of components the system can support (e.g., installed memory, not supported memory; etc.)
- v. The Additional Power Supply allowance may be applied for each redundant power supply used in the configuration.
- vi. For the purposes of determining Idle State power allowances, all memory capacities shall be rounded to the nearest GB.
- vii. The Additional I/O Device allowance may be applied for all I/O Devices over the Base Configuration (i.e., Ethernet devices additional to two ports greater than or equal to 1 Gigabit per second (Gbit/s), onboard Ethernet, plus any non-Ethernet I/O devices), including on-board I/O devices and add-in I/O devices installed through expansion slots. This allowance may be applied for each of the following types of I/O functionality: Ethernet, SAS, SATA, Fibre Channel and Infiniband.

424
425
426

Note: EPA has clarified in 3.6.1.vii above that the Additional I/O Device allowance may be applied to interfaces beyond Ethernet. Specifically, this list includes Ethernet (including subsets such as FoE and iSCSI), SAS, SATA, Fibre Channel and Infiniband, providing they meet requirements viii and ix, below.

427
428
429

viii. The Additional I/O Device allowance shall be calculated based upon the rated link speed of a single connection, rounded to the nearest Gbit. I/O devices with less than 1 Gbit speed do not qualify for the Additional I/O Device allowance.

430
431
432

ix. The Additional I/O Device allowance shall only be applied for I/O devices that are active/enabled upon shipment, and are capable of functioning when connected to an active switch.

433

Table 3: Base Idle State Power Allowances for 1S and 2S Servers

Category	Maximum Possible Number of Installed Processors (# P)	Managed Server	Base Idle State Power Allowance, P _{BASE} (watts)
A	1	No	47.0
B	1	Yes	57.0
C	2	No	92.0
D	2	Yes	142.0
Resilient	2	Yes	205.0

434
435
436

Note: EPA has included a Resilient category in Table 3 based on stakeholder provided data and additional internal analysis. This allowance is only applicable to computer server products that meet all of the requirements in the Resilient Server Definition found in Appendix B of this Eligibility Criteria.

437

Table 4: Additional Idle Power Allowances for Extra Components

System Characteristic	Applies To:	Additional Idle Power Allowance
Additional Power Supplies	Power supplies installed explicitly for power redundancy ^(v)	20 watts per Power Supply
Additional Hard Drives (including solid state drives)	Per installed hard drive	8.0 watts per Hard Drive
Additional Memory	Installed memory greater than 4 GB ^(vi)	0.75 watts per GB ^(vi)
Additional Buffered DDR Channel	Installed buffered DDR Channels greater than 8 channels (Resilient Servers only)	4.0 watts per Buffered DDR Channel
Additional I/O Devices ^{(viii), (ix)}	Installed Devices greater than two ports of ≥ 1 Gbit, onboard Ethernet	< 1Gbit: No Allowance = 1 Gbit: 2.0 watts / Active Port > 1 Gbit and < 10 Gbit: 4.0 watts / Active Port ≥ 10 Gbit: 8.0 watts / Active Port

438

439 **Note:** EPA has received stakeholder feedback that a Buffered DDR Channel adder is necessary to allow
440 highly configured two socket resilient server configurations to be assessed fairly for certification. Based
441 on stakeholder provided data and additional internal investigation, EPA is proposing a 4.0 watt per
442 Buffered DDR Channel adder for every installed channel greater than 8. The power consumption of the
443 first 8 Buffered DDR Channels are included in the base idle state power allowance for Resilient Servers
444 as defined in Table 3.

445
446 **Note:** EPA has removed Full Load efficiency criteria and data disclosure, as active state measurements
447 and reporting requirements will be based on the SERT rating tool in Version 2.0.

448 **3.7 Idle State Efficiency Criteria – Three-Socket (3S) and Four-Socket (4S) Servers**
449 **(neither Blade nor Multi-Node)**

450 3.7.1 Idle State Data Disclosure: Idle State power (P_{IDLE}) shall be measured and
451 reported, both in qualification materials and as required in Section 4.

452 **3.8 Idle State Efficiency Criteria – Blade Servers**

453 3.8.1 Idle State Data Disclosure: Idle State power (P_{IDLE}) shall be measured and reported, both in
454 qualification materials and as required in Section 4.

455 3.8.2 The testing of Blade Servers for compliance with 3.8.1 and **Error! Reference source not found.**
456 shall be carried out under all of the following conditions:

- 457 i. Power values shall be measured and reported using a half-populated Blade Chassis. Blade
458 Servers with asymmetric power domains shall round up to the nearest power domain as
459 guided by the manufacturer’s defined configuration recommendations. The number of blades
460 tested during the half-populated Blade Chassis test shall be reported in the Power and
461 Performance Data Sheet (PPDS).
- 462 ii. Power for a fully-populated blade chassis may be optionally measured and reported, provided
463 that half-populated chassis data is also provided.
- 464 iii. All Blade Servers installed in the Blade Chassis shall share the same configuration
465 (homogeneous).
- 466 iv. Per-blade power values shall be calculated using Equation 2.

467 **Equation 2: Calculation of Single Blade Power**

468
$$P_{BLADE} = \frac{P_{TOT_BLADE_SYS}}{N_{INST_BLADE_SRV}}$$

469 *Where:*

- 470 ▪ P_{BLADE} is the per-Blade Server Power (either Idle or Full-
471 load),
- 472 ▪ $P_{TOT_BLADE_SYS}$ is total measured power of the Blade System,
- 473 ▪ $N_{INST_BLADE_SRV}$ is the number of installed Blade Servers in
474 the tested Blade Chassis.
475

476 **Note:** EPA proposes that Blade Servers which have asymmetric power domains shall round up to the
477 nearest power domain as decided by the manufacturer when adhering to the half-populated Blade
478 Chassis testing requirement. The number of blades tested during the half-chassis test shall be reported in
479 the PPDS. The variety of power domain sizes, number of domains per chassis, chassis sizes, and
480 particular details of operation that may vary between manufacturers have necessitated this approach to
481 ensure that testing burden is reasonable and that test data accurately represents system capabilities as
482 deployed in the field. Manufacturers are still free to test fully populated blade chassis, in addition to half
483 chassis, if they wish to provide this information to purchasers.

484 3.9 Idle State Efficiency Criteria – Multi-Node Servers

485 3.9.1 Idle State Data Disclosure: Idle State power (P_{IDLE}) shall be measured and reported, both in
486 qualification materials and as required in Section 4, below.

487 3.9.2 The testing of Multi-Node Servers for compliance with 3.8.1 and **Error! Reference source not**
488 **found.** shall be carried out under all of the following conditions:

- 489 i. Power values shall be measured and reported using a fully-populated Multi-Node Chassis.
- 490 ii. All Multi-Node Servers in the Multi-Node Chassis shall share the same configuration
491 (homogeneous).
- 492 iii. Per-node power values shall be calculated using Equation 3.

493 Equation 3: Calculation of Single Node Power

$$494 P_{NODE} = \frac{P_{TOT_NODE_SYS}}{N_{INST_NODE_SRV}}$$

495 *Where:*

- 496 ▪ P_{NODE} is the per-Node Server Power (either Idle or Full-
497 load),
- 498 ▪ $P_{TOT_NODE_SYS}$ is total measured power of the Multi-Node
499 Server,
- 500 ▪ $N_{INST_NODE_SRV}$ is the number of installed Multi-Node
501 Servers in the tested Multi-Node Chassis.

502 **Note:** EPA has added a new section to clarify idle state efficiency criteria specifically for multi-node
503 servers in this Final Draft. The multi-node server criteria are similar to blade server criteria, but require
504 that the multi-node servers be tested with a fully-populated chassis. EPA understands that these products
505 are smaller than blade servers and are typically purchased and deployed fully stocked. The “Other
506 Testing Criteria” found in Section 3.9 of Draft 3 has been moved to Section 3.10 in the Final Draft.

507 3.10 Other Testing Criteria

508 3.10.1 APA Requirements: For all computer servers sold with APAs, the following criteria and provisions
509 apply:

- 510 i. For single configurations: All Idle State testing shall be conducted both with and without the
511 APAs installed. Idle Power measurements taken both with the APAs installed and removed
512 shall be submitted to EPA as part of ENERGY STAR qualification materials.
- 513 ii. For Product Families: Idle State testing shall be conducted both with and without the APAs
514 installed in the Maximum Power / High-end Performance Configuration found in 1.H)2).
515 Testing with and without the APAs installed may optionally be conducted and disclosed at the
516 other test points.

- 517 iii. Idle State power measurements taken both with the APAs installed and removed shall be
518 submitted to EPA as part of ENERGY STAR qualification materials. These measurements
519 shall be submitted for each individual APA product that is intended for sale with the qualified
520 configuration.
- 521 iv. Idle State power data with the APAs removed shall be used as P_{BASE} for the purposes of
522 qualification of the single configuration or Product Family test point.
- 523 v. The idle power consumption of each installed APA in qualified configurations shall not exceed
524 46 watts.
- 525 vi. The Idle State power consumption of each individual APA product sold with a qualified
526 configuration shall be reported in the PPDS.

527 **Note:** EPA has moved the definition of APA into Section 1 of this Final Draft. Recognizing that “add-in
528 compute” capability may be delivered by solutions other than GPUs, EPA continues to propose the use of
529 the more general term Auxiliary Processing Accelerators (APAs).

530 EPA received stakeholder feedback that the APA idle power allowance in Draft 3 of 46 watts for all APAs
531 was not sufficient and is instead proposing a maximum idle power of 46 watts *per* APA shipped with a
532 qualified configuration. This requirement will be accompanied with a new requirement that idle state
533 power consumption of each APA sold with a qualified configuration shall be reported in the PPDS. The 46
534 watt per APA proposed level in Draft 3 was informed by EPA’s research into power consumption of fully-
535 featured GPUs in the Workstation/Computer space.

536 The APA testing requirements above apply to all computer servers, including Blade and Multi-node
537 servers. Tests with APAs should be conducted on the maximum configuration of the product family. Each
538 additional model of APA that a manufacturer wishes to include in the product family must be separately
539 tested on this maximum configuration.

540 4 STANDARD INFORMATION REPORTING REQUIREMENTS

541 4.1 Power and Performance Datasheet (PPDS)

- 542 4.1.1 Data for a standardized Power and Performance Data Sheet (PPDS) shall be submitted to EPA
543 for each ENERGY STAR qualified Computer Server or Computer Server Product Family.
- 544 i. Partners are encouraged to provide one set of data for each ENERGY STAR qualified
545 product configuration, though EPA will also accept a data set for each qualified product
546 family.
- 547 ii. A product family PPDS must include data for all defined test points in 1.H)2), as applicable.
- 548 iii. Whenever possible, Partners must also provide a hyperlink to a more detailed power
549 calculator on their Web site that purchasers can use to understand power and performance
550 data for specific configurations within the product family.
- 551 4.1.2 Templates for the Power and Performance Data Sheet can be found on the ENERGY STAR Web
552 site at www.energystar.gov/products.

553 The PPDS contains the following information:

- 554
- 555 i. model name and number, identifying SKU and/or configuration ID;
- 556 ii. system characteristics (form factor, available sockets/slots, power specifications, etc.);
- 557 iii. system type (unmanaged, managed, scalable, etc.);

- 558 iv. system configuration(s) (including Low-end Performance Configuration, High-end
559 Performance Configuration, Minimum Power Configuration, Maximum Power Configuration,
560 and Typical Configuration for Product Family qualification);
- 561 v. data from required Active State Efficiency Criteria testing;
- 562 vi. power data for Idle and Full Load, estimated kWh/year, link to power calculator (where
563 available);
- 564 vii. available and enabled power saving features (e.g., power management);
- 565 viii. power consumption and performance data, along with guaranteed accuracy levels for all
566 power and temperature measurements, disclosure of the time period used for data averaging,
567 and a hyperlink to a detailed power calculator, as available;
- 568 ix. a list of selected data from the ASHRAE Thermal Report;
- 569 x. inlet air temperature measurements made prior to the start of testing, at the conclusion of idle
570 state testing, and at the conclusion of active testing;

571 **Note:** Based on stakeholder requests in response to Draft 3, EPA is requiring that manufacturers report
572 the air inlet temperature of the SUT at three times, 1) when the system is off prior to the start of testing 2)
573 at the conclusion of the idle state test and 3) at the conclusion of the active state testing. These values
574 will be reported in the thermal results section of the PPDS.

- 575 xi. for product family qualifications, a list of qualified configurations with qualified SKUs or
576 configuration IDs; and
 - 577 xii. for a blade server, a list of compatible blade chassis that meet ENERGY STAR qualification
578 criteria.
- 579 4.1.3 EPA may periodically revise this PPDS, as necessary, and will notify and invite stakeholder
580 engagement in such a revision process.

581 **5 STANDARD PERFORMANCE DATA MEASUREMENT AND OUTPUT** 582 **REQUIREMENTS**

583 **5.1 Measurement and Output**

- 584 5.1.1 A computer server must provide data on input power consumption (W), inlet air temperature (°C),
585 and utilization of all logical CPUs. Data must be made available in a published or user-accessible
586 format that is readable by third-party, non-proprietary management software over a standard
587 network. For blade and multi-node servers and systems, data may be aggregated at the chassis
588 level.
- 589 5.1.2 Computer servers classified as Class B equipment as set out in EN 55022:2006 are exempt from
590 the requirements to provide data on input power consumption and inlet air temperature in 5.1.1.
591 Class B refers to household and home office equipment (intended for use in the domestic
592 environment). All computer servers in the program must meet the requirement and conditions to
593 report utilization of all logical CPUs.

594 **5.2 Reporting Implementation**

- 595 5.2.1 Products may use either embedded components or add-in devices that are packaged with the
596 computer server to make data available to end users (e.g., a service processor, embedded power
597 or thermal meter (or other out-of-band technology), or pre-installed OS);

598 5.2.2 Products that include a pre-installed OS must include all necessary drivers and software for end
599 users to access standardized data as specified in this document. Products that do not include a
600 pre-installed OS must be packaged with printed documentation of how to access registers that
601 contain relevant sensor information. This requirement may be met via either printed materials,
602 electronic documentation provided with the computer server, or information publically available on
603 the Partner’s website where information about the computer server is found.

604 5.2.3 When an open and universally available data collection and reporting standard becomes
605 available, manufacturers should incorporate the universal standard into their systems;

606 5.2.4 Evaluation of the accuracy (5.3) and sampling (5.4) requirements shall be completed through
607 review of data from component product datasheets. If this data is absent, Partner declaration
608 shall be used to evaluate accuracy and sampling.

609 **5.3 Measurement Accuracy**

610 5.3.1 *Input power:* Measurements must be reported with accuracy of at least $\pm 5\%$ of the actual value,
611 with a maximum level of accuracy of $\pm 10W$ for each installed PSU (i.e., power reporting accuracy
612 for each power supply is never required to be better than ± 10 watts) through the operating range
613 from Idle to full power;

614 5.3.2 *Processor utilization:* Utilization must be estimated for each logical CPU that is visible to the OS
615 and must be reported to the operator or user of the computer server through the operating
616 environment (OS or hypervisor);

617 5.3.3 *Inlet air temperature:* Measurements must be reported with an accuracy of at least $\pm 2^{\circ}C$.

618 **5.4 Sampling Requirements**

619 5.4.1 *Input power and processor utilization:* Input power and processor utilization measurements must
620 be sampled internally to the computer server at a rate of greater than or equal to measurement
621 per contiguous 10 second period. A rolling average, encompassing a period of no more than 30
622 seconds, must be sampled internally to the computer server at a frequency of greater than or
623 equal to once per ten seconds.

624 5.4.2 *Inlet air temperature:* Inlet air temperature measurements must be sampled internally to the
625 computer server at a rate of greater than or equal to 1 measurement every 10 seconds.

626 5.4.3 *Time stamping:* Systems that implement time stamping of environmental data shall sample
627 internally to the computer server data at a rate of greater than or equal to 1 measurement every
628 30 seconds.

629 5.4.4 *Management Software:* All sampled measurements shall be made available to external
630 management software either via an on-demand pull method, or via a coordinated push
631 method. In either case the system’s management software is responsible for establishing the
632 data delivery time scale while the computer server is responsible to assuring data delivered
633 meets the above sampling and currency requirements.

634 **Note:** EPA has revised the language in Section 5.4 to provide clarity on sampling and currency of power
635 and temperature requirements for computer servers. The technical requirements and intent of the
636 language remain the same. All changes are to improve clarity.

637 **6 TESTING**

638 **6.1 Test Methods**

639 6.1.1 When testing Computer Server products, the test methods identified in Table 5 shall be used to
640 determine ENERGY STAR qualification.

641

Table 5: Test Methods for ENERGY STAR Qualification

Product Type or Component	Test Method
All	ENERGY STAR Test Method for Computer Servers, Final Draft (Rev. Jan-2013)
All	Standard Performance Evaluation Corporation (SPEC) Server Efficiency Rating Tool (SERT), Beta 3 (Release Candidate 1), Rev. Nov 2012

642
643

6.1.2 When testing Computer Server products, SUTs must have all Processor Sockets populated during testing.

644
645
646

- i. If a Computer Server cannot support populating all Processor Sockets during testing, then the system must be populated to its maximum functionality. These systems will be subject to the base idle state power allowance based on the number of sockets in the system.

647
648
649

Note: EPA received stakeholder feedback on computer server products which can only function with one processor but use two socket hardware. EPA is proposing to test these systems with one socket populated but require them to meet the two socket idle state power allowance.

650

6.2 Number of Units Required for Testing

651

6.2.1 Representative Models shall be selected for testing per the following requirements:

652
653
654

- i. For qualification of an individual product configuration, the unique configuration that is intended to be marketed and labeled as ENERGY STAR is considered the Representative Model.

655
656
657
658

- ii. For qualification of a product family of all product types, one product configuration for each of the five points identified in definitions 1.H)2) within the family are considered Representative Models. All such representative models shall have the same Common Product Family Attributes as defined in 1.H)1).

659

6.3 Qualifying Families of Products

660
661
662
663

6.3.1 Partners are encouraged to test and submit data on individual product configurations for qualification to ENERGY STAR. However, a Partner may qualify multiple product configurations under one Product Family designation if each configuration within the family meets one of the following requirements:

664
665
666

- i. Individual products are built on the same platform, are eligible under and meet the same specific requirements in this specification, and are identical in every respect to the tested, representative product configuration except for housing and color; or

667
668

- ii. Individual products meet the requirements of a product family, as defined in Section H), above. In this case, partners must test and submit data as required in Section 6.2.1ii.

669
670

6.3.2 Partners are required to submit a Power and Performance Data Sheet for each product family that is submitted for qualification.

671
672

6.3.3 All product configurations within a product family that is submitted for qualification must meet ENERGY STAR requirements, including products for which data was not reported.

673 **7 EFFECTIVE DATE**

674 7.1.1 Effective Date: The Version 2.0 ENERGY STAR Computer Servers specification shall take effect
675 on November 20, 2013. To qualify for ENERGY STAR, a product model shall meet the ENERGY
676 STAR specification in effect on its date of manufacture. The date of manufacture is specific to
677 each unit and is the date on which a unit is considered to be completely assembled.

678 **Note:** EPA intends to publish the final ENERGY STAR Computer Servers Version 2.0 specification by
679 February 20, 2013.

680 7.1.2 Future Specification Revisions: EPA reserves the right to change this specification should
681 technological and/or market changes affect its usefulness to consumers, industry, or the
682 environment. In keeping with current policy, revisions to the specification are arrived at through
683 stakeholder discussions. In the event of a specification revision, please note that the ENERGY
684 STAR qualification is not automatically granted for the life of a product model.

685 **8 CONSIDERATIONS FOR FUTURE REVISIONS**

686

687 **8.1 TBD**

688

689
690
691

APPENDIX A: Sample Calculations

692
693

Note: This appendix will ultimately include sample calculations for reference in calculating performance levels for products covered in this specification.

694
695
696

697
698
699

APPENDIX B: IDENTIFYING RESILIENT SERVER CLASS

700

Note: This appendix describes the feature set for identification of Resilient Servers.

701

a) *Processor RAS and Scalability* - All of the following shall be supported:

702
703

(1) *Processor RAS:* The processor must have capabilities to detect, correct, and contain data errors, as described by all of the following:

704
705

(a) Error detection on L1 caches, directories and address translation buffers using parity protection;

706
707
708

(b) Single bit error correction using ECC on caches that can contain modified data. Corrected data is delivered to the recipient (i.e., error correction is not used just for background scrubbing);

709
710
711
712

(c) Error recovery and containment by means of (1) processor checkpoint retry and recovery, (2) data poison indication (tagging) and propagation, or (3) both. The mechanisms notify the OS or hypervisor to contain the error within a process or partition, thereby reducing the need for system reboots; and

713
714
715
716

(d) (1) Capable of autonomous error mitigation actions within processor hardware, such as disabling of the failing portions of a cache, (2) support for predictive failure analysis by notifying the OS, hypervisor, or service processor of the location and/or root cause of errors, or (3) both.

717
718
719
720
721

(2) The processor technology used in resilient and scalable servers is designed to provide additional capability and functionality without additional chipsets, enabling them to be designed into systems with 4 or more processor sockets. The processors have additional infrastructure to support extra, built-in processor busses to support the demand of larger systems.

722
723
724
725
726

(3) The server provides high bandwidth I/O interfaces for connecting to external I/O expansion devices or remote I/O without reducing the number of processor sockets that can be connected together. These may be proprietary interfaces or standard interfaces such as PCIe. The high performance I/O controller to support these slots may be embedded within the main processor socket or on the system board.

727
728

b) *Memory RAS and Scalability* - All of the following capabilities and characteristics shall be present:

729

(1) Provides memory fault detection and recovery through Extended ECC;

730

(2) In x4 DIMMs, recovery from failure of two adjacent chips in the same rank;

731
732
733

(3) Memory migration: Failing memory can be proactively de-allocated and data migrated to available memory. This can be implemented at the granularity of DIMMs or logical memory blocks. Alternatively, memory can also be mirrored;

734
735
736
737
738
739
740
741

(4) Uses memory buffers for connection of higher speed processor -memory links to DIMMs attached to lower speed DDR channels. Memory buffer can be a separate, standalone buffer chip which is integrated on the system board, or integrated on custom-built memory cards. The use of the buffer chip is required for extended DIMM support; they allow larger memory capacity due to support for larger capacity DIMMs, more DIMM slots per memory channel, and higher memory bandwidth per memory channel than direct-attached DIMMs. The memory modules may also be custom-built, with the memory buffers and DRAM chips integrated on the same card;

742

(5) Uses resilient links between processors and memory buffers with mechanisms to

- 743 recover from transient errors on the link; and
- 744 (6) Lane sparing in the processor-memory links. One or more spare lanes are available
745 for lane failover in the event of permanent error.
- 746 c) *Power Supply RAS*: All PSUs installed or shipped with the server shall be redundant and
747 concurrently maintainable. The redundant and repairable components may also be
748 housed within a single physical power supply, but must be repairable without requiring
749 the system to be powered down. Support must be present to operate the system in
750 degraded mode when power delivery capability is degraded due to failures in the power
751 supplies or input power loss.
- 752 d) *Thermal and Cooling RAS*: All active cooling components, such as fans or water-based
753 cooling, shall be redundant and concurrently maintainable. The processor complex must
754 have mechanisms to allow it to be throttled under thermal emergencies. Support must be
755 present to operate the system in degraded mode when thermal emergencies are
756 detected in system components.

757 **Note:** The thermal and cooling RAS requirements have been revised to only apply to active cooling
758 components.

- 759 e) *System Resiliency* – no fewer than six of the following characteristics shall be present in
760 the server:
- 761 (1) Support of redundant storage controllers or redundant path to external storage;
762 (2) Redundant service processors;
763 (3) Redundant dc-dc regulator stages after the power supply outputs;
764 (4) The server hardware supports runtime processor de-allocation;
765 (5) I/O adapters or hard drives are hot-swappable;
766 (6) Provides end to end bus error retry on processor to memory or processor to
767 processor interconnects;

768 **Note:** Based on stakeholder feedback, the link level retry requirement has been replaced with end to end
769 bus error retry, which is only available on current resilient server architectures.

- 770 (7) Supports on-line expansion/retraction of hardware resources without the need for
771 operating system reboot (“on-demand” features);
- 772 (8) Processor Socket migration: With hypervisor and/or OS assistance, tasks executing
773 on a processor socket can be migrated to another processor socket without the need
774 for the system to be restarted;
- 775 (9) Memory patrol or background scrubbing is enabled for proactive detection and
776 correction of errors to reduce the likelihood of uncorrectable errors; and
- 777 (10) Internal storage resiliency: Resilient systems have some form of RAID hardware in
778 the base configuration, either through support on the system board or a dedicated
779 slot for a RAID controller card for support of the server’s internal drives.
- 780 f) *System Scalability* – All of the following shall be present in the server:
- 781 (1) Higher memory capacity: ≥ 8 DDR3 or DDR4 DIMM Ports per socket, with resilient
782 links between the processor socket and memory buffers; and
- 783 (2) Greater I/O expandability: Larger base I/O infrastructure and support a higher
784 number of I/O slots. Provide at least 32 dedicated PCIe Gen 2 lanes or equivalent I/O
785 bandwidth, with at least one x16 slot or other dedicated interface to support external
786 PCIe, proprietary I/O interface or other industry standard I/O interface.