



ENERGY STAR® Program Requirements Product Specification for Computer Servers

Eligibility Criteria Final Draft, Version 3.0

1 Following is the Final Draft, Version 3.0 ENERGY STAR Product Specification for Computer Servers. A
2 product shall meet all of the identified criteria if it is to earn the ENERGY STAR.

3 **1 DEFINITIONS**

4 A) Product Types:

- 5 1) Computer Server: A computer that provides services and manages networked resources for
6 client devices (e.g., desktop computers, notebook computers, thin clients, wireless devices,
7 PDAs, IP telephones, other computer servers, or other network devices). A computer server
8 is sold through enterprise channels for use in data centers and office/corporate environments.
9 A computer server is primarily accessed via network connections, versus directly-connected
10 user input devices such as a keyboard or mouse. For purposes of this specification, a
11 computer server must meet **all** of the following criteria:
- 12 A. is marketed and sold as a Computer Server;
 - 13 B. is designed for and listed as supporting one or more computer server operating systems
14 (OS) and/or hypervisors;
 - 15 C. is targeted to run user-installed applications typically, but not exclusively, enterprise in
16 nature;
 - 17 D. provides support for error-correcting code (ECC) and/or buffered memory (including both
18 buffered dual in-line memory modules (DIMMs) and buffered on board (BOB)
19 configurations).
 - 20 E. is packaged and sold with one or more ac-dc or dc-dc power supplies; and
 - 21 F. is designed such that all processors have access to shared system memory and are
22 visible to a single OS or hypervisor.
- 23 2) Blade System: A system comprised of a blade chassis and one or more removable blade
24 servers and/or other units (e.g., blade storage, blade network equipment). Blade systems
25 provide a scalable means for combining multiple blade server or storage units in a single
26 enclosure, and are designed to allow service technicians to easily add or replace (hot-swap)
27 blades in the field.
- 28 A. Blade Server: A computer server that is designed for use in a blade chassis. A blade
29 server is a high-density device that functions as an independent computer server and
30 includes at least one processor and system memory, but is dependent upon shared blade
31 chassis resources (e.g., power supplies, cooling) for operation. A processor or memory
32 module that is intended to scale up a standalone server is not considered a Blade Server.
 - 33 (1) *Multi-bay Blade Server:* A blade server requiring more than one bay for installation in
34 a blade chassis.
 - 35 (2) *Single-wide Blade Server:* A blade server requiring the width of a standard blade
36 server bay.

- 37 (3) *Double-wide Blade Server*: A blade server requiring twice the width of a standard
38 blade server bay.
- 39 (4) *Half-height Blade Server*: A blade server requiring one half the height of a standard
40 blade server bay.
- 41 (5) *Quarter-height Blade Server*: A blade server requiring one quarter the height of a
42 standard server bay.
- 43 (6) *Multi-Node Blade Server*: A blade server which has multiple nodes. The blade server
44 itself is hot swappable, but the individual nodes are not.
- 45 B. Blade Chassis: An enclosure that contains shared resources for the operation of blade
46 servers, blade storage, and other blade form-factor devices. Shared resources provided
47 by a chassis may include power supplies, data storage, and hardware for dc power
48 distribution, thermal management, system management, and network services.
- 49 C. Blade Storage: A storage device that is designed for use in a blade chassis. A blade
50 storage device is dependent upon shared blade chassis resources (e.g., power supplies,
51 cooling) for operation.
- 52 3) Fully Fault Tolerant Server: A computer server that is designed with complete hardware
53 redundancy, in which every computing component is replicated between two nodes running
54 identical and concurrent workloads (i.e., if one node fails or needs repair, the second node
55 can run the workload alone to avoid downtime). A fully fault tolerant server uses two systems
56 to simultaneously and repetitively run a single workload for continuous availability in a
57 mission critical application.
- 58 4) Resilient Server: A computer server designed with extensive Reliability, Availability,
59 Serviceability (RAS) and scalability features integrated in the micro architecture of the
60 system, CPU and chipset. For purposes of ENERGY STAR certification under this
61 specification, a Resilient Server shall have the following characteristics:
- 62 A. Processor RAS: The processor must have capabilities to detect, correct, and contain data
63 errors, as described by all of the following:
- 64 (1) Error recovery by means of instruction retry for certain processor faults;
- 65 (2) Error detection on L1 caches, directories, and address translation buffers using parity
66 protection; and
- 67 (3) Single bit error correction (or better) on caches that can contain modified data.
68 Corrected data is delivered to the recipient as part of the request completion.
- 69 B. System Recovery & Resiliency: No fewer than six of the following characteristics shall be
70 present in the server:
- 71 (1) Error recovery and containment by means of (a) data poison indication (tagging) and
72 propagation which includes mechanism to notify the OS or hypervisor to contain the
73 error, thereby reducing the need for system reboots and (b) containment of
74 address/command errors by preventing possibly contaminated data from being
75 committed to permanent storage;
- 76 (2) The processor technology is designed to provide additional capability and
77 functionality without additional chipsets, enabling the design into systems with four or
78 more processor sockets;
- 79 (3) Memory Mirroring: A portion of available memory can be proactively partitioned such
80 that a duplicate set may be utilized upon non-correctable memory errors. This can be
81 implemented at the granularity of DIMMs or logical memory blocks;
- 82 (4) Memory Sparing: A portion of available memory may be pre-allocated to a spare
83 function such that data may be migrated to the spare upon a perceived impending
84 failure;

- 85 (5) Support for making additional resources available without the need for a system
86 restart. This may be achieved either by processor (cores, memory, I/O) on-lining
87 support, or by dynamic allocation/deallocation of processor cores, memory, and I/O
88 to a partition;
- 89 (6) Support of redundant I/O devices (storage controllers, networking controllers);
- 90 (7) Has I/O adapters or storage devices that are hot-swappable;
- 91 (8) Can identify failing processor-to-processor lane(s) and dynamically reduce the width
92 of the link in order to use only non-failing lanes or provide a spare lane for failover
93 without disruption;
- 94 (9) Capability to partition the system such that it enables running instances of the OS or
95 hypervisor in separate partitions. Partition isolation is enforced by the platform and/or
96 hypervisor and each partition is capable of independently booting; or
- 97 (10) Uses memory buffers for connection of higher speed processor-memory links to
98 DIMMs attached to lower speed DDR channels. Memory buffer can be a separate,
99 standalone buffer chip which is integrated on the system board or integrated on
100 custom-built memory cards.

101 C. Power Supply RAS: All power supplies installed or shipped with the server shall be
102 redundant and concurrently maintainable. The redundant and repairable components
103 may also be housed within a single physical power supply, but must be repairable without
104 requiring the system to be powered down. Support must be present to operate the
105 system in a degraded mode.

106 D. Thermal and Cooling RAS: All active cooling components shall be redundant and
107 concurrently maintainable. The processor complex must have mechanisms to allow it to
108 be throttled under thermal emergencies. Support must be present to operate the system
109 in a degraded mode when thermal emergencies are detected in the system components.

110 5) **Note**: EPA has changed the language “and” at the end of the B.9 portion of the resilient
111 server definition to “or” to clarify that options (9) and (10) are not to be read as combined but
112 rather separate items in the list. Multi-node Server: A computer server that is designed with
113 two or more independent server nodes that share a single enclosure and one or more power
114 supplies. In a multi-node server, power is distributed to all nodes through shared power
115 supplies. Server nodes in a multi-node server are not designed to be hot-swappable.

116 A. Dual-node Server: A common multi-node server configuration consisting of two server
117 nodes.

118 6) Server Appliance: A computer server that is bundled with a pre-installed OS and application
119 software that is used to perform a dedicated function or set of tightly coupled functions.
120 Server appliances deliver services through one or more networks (e.g., IP or SAN), and are
121 typically managed through a web or command line interface. Server appliance hardware and
122 software configurations are customized by the vendor to perform a specific task (e.g., name
123 services, firewall services, authentication services, encryption services, and voice-over-IP
124 (VoIP) services), and are not intended to execute user-supplied software.

125 7) High Performance Computing (HPC) System: A computing system which is designed and
126 optimized to execute highly parallel applications for high performance, deep learning, or
127 artificial intelligence applications. HPC systems feature clustered nodes often featuring high
128 speed inter-processing interconnects as well as high memory capability and bandwidth. HPC
129 systems may be purposely built, or assembled from more commonly available computer
130 servers. HPC systems must meet ALL the following criteria:

131 A. Marketed and sold as a Computer Server optimized for higher performance computing,
132 augmented or artificial intelligence, or deep learning applications;

133 B. Designed (or assembled) and optimized to execute highly parallel applications;

- 134 C. Consist of multiple computing nodes, clustered primarily to increase computational
135 capability;
- 136 D. Includes high speed inter-processing interconnections between nodes.

137 **Note:** EPA has clarified that HPC products shall be designed to execute highly parallel high performance,
138 deep learning “or” artificial intelligence applications rather than “and” as stated in Draft 3.

139 8) Direct Current (dc) Server: A computer server that is designed solely to operate on a dc
140 power source.

141 9) Large Server: A resilient/scalable server which ships as a pre-integrated/pre-tested system
142 housed in one or more full frames or racks and that includes a high connectivity I/O
143 subsystem with a minimum of 32 dedicated I/O slots.

144 B) Computer Server Form Factors:

145 1) Rack-mounted Server: A computer server that is designed for deployment in a standard 19-
146 inch data center rack as defined by EIA-310, IEC 60297, or DIN 41494. For the purposes of
147 this specification, a blade server is considered under a separate category and excluded from
148 the rack-mounted category.

149 2) Pedestal/Tower Server: A self-contained computer server that is designed with PSUs,
150 cooling, I/O devices, and other resources necessary for stand-alone operation. The frame of
151 a pedestal server is similar to that of a tower client computer.

152 C) Computer Server Components:

153 1) Power Supply Unit (PSU): A device that converts ac or dc input power to one or more dc
154 power outputs for the purpose of powering a computer server. A computer server PSU must
155 be self-contained and physically separable from the motherboard and must connect to the
156 system via a removable or hard-wired electrical connection.

157 A. Ac-Dc Power Supply: A PSU that converts line-voltage ac input power into one or more
158 dc power outputs for the purpose of powering a computer server.

159 B. Dc-Dc Power Supply: A PSU that converts line-voltage dc input power to one or more dc
160 outputs for the purpose of powering a computer server. For purposes of this specification,
161 a dc-dc converter (also known as a voltage regulator) that is internal to a computer server
162 and is used to convert a low voltage dc (e.g., 12 V dc) into other dc power outputs for use
163 by computer server components is not considered a dc-dc power supply.

164 C. Single-output Power Supply: A PSU that is designed to deliver the majority of its rated
165 output power to one primary dc output for the purpose of powering a computer server.
166 Single-output PSUs may offer one or more standby outputs that remain active whenever
167 connected to an input power source. For purposes of this specification, the total rated
168 power output from any additional PSU outputs that are not primary and standby outputs
169 shall be no greater than 20 watts. PSUs that offer multiple outputs at the same voltage as
170 the primary output are considered single-output PSUs unless those outputs (1) are
171 generated from separate converters or have separate output rectification stages, or (2)
172 have independent current limits.

173 D. Multi-output Power Supply: A PSU that is designed to deliver the majority of its rated
174 output power to more than one primary dc output for the purpose of powering a computer
175 server. Multi-output PSUs may offer one or more standby outputs that remain active
176 whenever connected to an input power source. For purposes of this specification, the
177 total rated power output from any additional PSU outputs that are not primary and
178 standby outputs shall be no greater than or equal to 20 watts.

179
180
181

Note: EPA received stakeholder feedback requesting to harmonize the multi-output PSU language regarding non-primary or standby outputs with the language used in the single-output PSU definition. EPA has included this proposed change in the Final Draft.

182
183
184
185
186

2) I/O Device: A device which provides data input and output capability between a computer server and other devices. An I/O device may be integral to the computer server motherboard or may be connected to the motherboard via expansion slots (e.g., PCI, PCIe). Examples of I/O devices include discrete Ethernet devices, InfiniBand devices, RAID/SAS controllers, and Fibre Channel devices.

187
188
189

A. I/O Port: Physical circuitry within an I/O device where an independent I/O session can be established. A port is not the same as a connector receptacle; it is possible that a single connector receptacle can service multiple ports of the same interface.

190
191
192

3) Motherboard: The main circuit board of the server. For purposes of this specification, the motherboard includes connectors for attaching additional boards and typically includes the following components: processor, memory, BIOS, and expansion slots.

193
194
195
196
197

4) Processor: The logic circuitry that responds to and processes the basic instructions that drive a server. For purposes of this specification, the processor is the central processing unit (CPU) of the computer server. A typical CPU is a physical package to be installed on the server motherboard via a socket or direct solder attachment. The CPU package may include one or more processor cores.

198
199

5) Memory: For purposes of this specification, memory is a part of a server external to the processor in which information is stored for immediate use by the processor.

200
201
202
203
204
205

6) Storage Device: A collective term for disk drives (HDDs), solid state drives (SSDs), tapes cartridges, and any other mechanisms providing non-volatile data storage. This definition is specifically intended to exclude aggregating storage elements such as RAID array subsystems, robotic tape libraries, filers, and file servers. Also excluded are storage devices which are not directly accessible by end-user application programs, and are instead employed as a form of internal cache.

206 D) Other Datacenter Equipment:

207
208
209

1) Large Network Equipment: A device whose primary function is to pass data among various network interfaces/ports, is mountable in a Standard Equipment Rack, supports network management protocols (e.g. SNMP) and contains at least one of the following features:

210

A. Contains more than eleven (11) physical network ports.

211

B. Total aggregate port throughput of the product is greater than 12 Gb/s.

212
213

Note: EPA has updated the previous Network Equipment definition to align with the Large Network Equipment definition found in the ENERGY STAR Version 1.0 Large Network Equipment specification.

214
215
216
217
218
219
220
221
222
223
224

2) Storage Product: A fully-functional storage system that supplies data storage services to clients and devices attached directly or through a network. Components and subsystems that are an integral part of the storage product architecture (e.g., to provide internal communications between controllers and disks) are considered to be part of the storage product. In contrast, components that are normally associated with a storage environment at the data center level (e.g., devices required for operation of an external SAN) are not considered to be part of the storage product. A storage product may be composed of integrated storage controllers, storage devices, embedded network elements, software, and other devices. While storage products may contain one or more embedded processors, these processors do not execute user-supplied software applications but may execute data-specific applications (e.g., data replication, backup utilities, data compression, install agents).

225 3) Uninterruptible Power Supply (UPS)¹: Combination of convertors, switches, and energy
226 storage devices (such as batteries) constituting a power system for maintaining continuity of
227 load power in case of input power failure.

228 E) Operational Modes and Power States:

229 1) Idle State: The operational state in which the OS and other software have completed loading,
230 the computer server is capable of completing workload transactions, but no active workload
231 transactions are requested or pending by the system (i.e., the computer server is operational,
232 but not performing any useful work). For systems where ACPI standards are applicable, Idle
233 State correlates only to ACPI System Level S0.

234 2) Active State: The operational state in which the computer server is carrying out work in
235 response to prior or concurrent external requests (e.g., instruction over the network). Active
236 state includes **both** (1) active processing and (2) data seeking/retrieval from memory, cache,
237 or internal/external storage while awaiting further input over the network.

238 F) Other Key Terms:

239 1) Controller System: A computer or computer server that manages a benchmark evaluation
240 process. The controller system performs the following functions:

241 A. start and stop each segment (phase) of the performance benchmark;

242 B. control the workload demands of the performance benchmark;

243 C. start and stop data collection from the power analyzer so that power and performance
244 data from each phase can be correlated;

245 D. store log files containing benchmark power and performance information;

246 E. convert raw data into a suitable format for benchmark reporting, submission and
247 validation; and

248 F. collect and store environmental data, if automated for the benchmark.

249 2) Network Client (Testing): A computer or computer server that generates workload traffic for
250 transmission to a unit under test (UUT) connected via a network switch.

251 3) RAS Features: An acronym for reliability, availability, and serviceability features. The three
252 primary components of RAS as related to a computer server are defined as follows:

253 A. *Reliability Features*: Features that support a server's ability to perform its intended
254 function without interruption due to component failures (e.g., component selection,
255 temperature and/or voltage de-rating, error detection and correction).

256 B. *Availability Features*: Features that support a server's ability to maximize operation at
257 normal capacity for a given duration of downtime (e.g., redundancy [both at micro- and
258 macro-level]).

259 C. *Serviceability Features*: Features that support a server's ability to be serviced without
260 interrupting operation of the server (e.g., hot plugging).

261 4) Server Processor Utilization: The ratio of processor computing activity to full-load processor
262 computing activity at a specified voltage and frequency, measured instantaneously or with a
263 short term average of use over a set of active and/or idle cycles.

264 5) Hypervisor: A type of hardware virtualization technique that enables multiple guest operating
265 systems to run on a single host system at the same time.

266 6) Auxiliary Processing Accelerators (APAs): An additional compute device installed in the

¹ Input power failure occurs when voltage and frequency are outside rated steady-state and transient tolerance bands or when distortion or interruptions are outside the limits specified for the UPS.

267 computer server that handles parallelized workloads in place of the CPU. This includes, but is
268 not limited to, General Purpose Graphics Processing Units (GPGPUs) and Field
269 Programmable Gate Array (FPGA) chips. There are two specific types of APAs used in
270 servers:

- 271 A. Expansion APA: An APA that is an add-in card installed in an add-in expansion slot (e.g.,
272 GPGPUs installed in a PCI slot). An expansion APA add-in card may include one or more
273 APAs and/or separate, dedicated removable switches.
- 274 B. Integrated APA: An APA that is integrated into the motherboard or CPU package.

275 **Note:** EPA has updated the APA definition to account for newer technologies in this space and to clarify
276 that expandable APAs may include multiple accelerators as well as dedicated removable switches in their
277 implementation.

278 7) Buffered DDR Channel: Channel or Memory Port connecting a Memory Controller to a
279 defined number of memory devices (e.g., DIMMs) in a computer server. A typical computer
280 server may contain multiple Memory Controllers, which may in turn support one or more
281 Buffered DDR Channels. As such, each Buffered DDR Channel serves only a fraction of the
282 total addressable memory space in a computer server.

283 G) Product Family: A high-level description referring to a group of computers sharing one
284 chassis/motherboard combination that often contains hundreds of possible hardware and software
285 configurations. Products within a product family may differ in color.

286 1) Common Product Family Attributes: A set of features common to all models/configurations
287 within a product family that constitute a common basic design. All models/configurations
288 within a product family must share the following:

- 289 A. Be from the same model line or machine type;
- 290 B. Either share the same form factor (i.e., rack-mounted, blade, pedestal) or share the same
291 mechanical and electrical designs with only superficial mechanical differences to enable
292 a design to support multiple form factors;
- 293 C. Either share processors from a single defined processor series or share processors that
294 plug into a common socket type. All configurations shipped as ENERGY STAR within the
295 product family shall contain the same number of populated sockets used during testing. A
296 product family can be defined for a server with only partially populated sockets (e.g. one
297 processor populated in a two socket processor system) as long as the configuration(s)
298 are tested as a separately certified product family, as required, and meet the active
299 efficiency limit for the number of populated sockets within that separate family.

300 **Note:** EPA has clarified that product families can be certified using single populated sockets in a two
301 socket server, so long as all the configurations in that family only populate a single socket, and that all
302 configurations in that family meet the applicable single socket active requirements. If, however, this two
303 socket server has two sockets utilized, it must be certified as a separate family.

304 D. Share PSUs that perform with efficiencies greater than or equal to the efficiencies at all
305 required load points specified in Section 3.2 (i.e., 10%, 20%, 50%, and 100% of
306 maximum rated load for single-output; 20%, 50%, and 100% of maximum rated load for
307 multi-output).

308 E. Have all memory channels populated with the same model DIMM. In all cases, the
309 minimum memory capacity is the number of memory channels in the server multiplied by
310 the minimum DIMM size offered in the family.

- 311 2) Product Family Tested Configurations²:
- 312 A. Low-end Performance Configuration: The combination of Processor Socket Power,
 313 PSUs, Memory, Storage Devices, and I/O devices that represents the lowest-
 314 performance computing platform within the Product Family. This configuration shall
 315 include the lowest processor performance per socket, as represented by the lowest
 316 numerical value resulting from the multiplication of the core count by the frequency in
 317 GHz, offered for sale and capable of meeting ENERGY STAR requirements.³ It shall also
 318 include a memory capacity at least equal to the number of DIMM slots in the server
 319 multiplied by the smallest DIMM size offered in the family.
- 320 B. High-end Performance Configuration: The combination of Processor Socket Power,
 321 PSUs, Memory, Storage Devices, and I/O devices that represents the highest-
 322 performance computing platform within the Product Family. This configuration shall
 323 include the highest processor performance per socket, as represented by the highest
 324 numerical value resulting from the multiplication of the core count by the frequency in
 325 GHz, offered for sale and capable of meeting ENERGY STAR requirements.² It shall also
 326 include a memory capacity equal to the value found in Equation 1 below:

327 **Equation 1: Minimum Memory Capacity of High-end Performance Configuration**

328
$$Mem_Capacity_High \geq 3 \times (\# \text{ of Sockets} \times \# \text{ of Physical Cores} \times \# \text{ Threads per Core})$$

- 329 C. Typical Configuration: A product configuration that lies between the Low-end
 330 Performance and High-end Performance configurations and is representative of a
 331 deployed product with high volume sales. It shall also include a memory capacity equal to
 332 the value found in Equation 2 below:

333 **Equation 2: Minimum Memory Capacity of Typical Configuration**

334
$$Mem_Capacity_Typ \geq 2 \times (\# \text{ of Sockets} \times \# \text{ of Physical Cores} \times \# \text{ Threads per Core})$$

335 **Note:** EPA has added a footnote above to clarify that products may be certified as a single configuration
 336 in the same manner as they were in Version 2.1.

337 **2 SCOPE**

338 **2.1 Included Products**

- 339 2.1.1 A product must meet the definition of a Computer Server provided in *Section 1* of this document
 340 to be eligible for ENERGY STAR certification under this specification. Eligibility under Version 3.0
 341 is limited to Blade-, Multi-node, Rack-mounted, or Pedestal form factor computer servers with no
 342 more than four processor sockets in the computer server (or per blade or node in the case of
 343 blade or multi-node servers). Products explicitly excluded from Version 3.0 are identified in
 344 *Section 2.2*.

² A single product configuration may be certified alone without a family.

³ Processor performance per socket = [# of processor cores] x [processor clock speed (GHz)], where # of cores represents the number of physical cores and processor clock speed represents the Max TDP core frequency as reported by SERT for a given processor.

345 **2.2 Excluded Products**

346 2.2.1 Products that are covered under other ENERGY STAR product specifications are not eligible for
347 certification under this specification. The list of specifications currently in effect can be found at
348 www.energystar.gov/products.

349 2.2.2 The following products are not eligible for certification under this specification:

- 350 i. Computer Servers shipped with Integrated APAs;
- 351 ii. Fully Fault Tolerant Servers;
- 352 iii. Server Appliances;
- 353 iv. High Performance Computing Systems;
- 354 v. Large Servers;
- 355 vi. Storage Products including Blade Storage; and
- 356 vii. Large Network Equipment.

357 **3 CERTIFICATION CRITERIA**

358 **3.1 Significant Digits and Rounding**

359 3.1.1 All calculations shall be carried out with directly measured (unrounded) values.

360 3.1.2 Unless otherwise specified, compliance with specification limits shall be evaluated using directly
361 measured or calculated values without any benefit from rounding.

362 3.1.3 Directly measured or calculated values that are submitted for reporting on the ENERGY STAR
363 website shall be rounded to the nearest significant digit as expressed in the corresponding
364 specification limit.

365 **3.2 Power Supply Requirements**

366 3.2.1 Power supply test data and test reports from testing entities recognized by EPA to perform power
367 supply testing shall be accepted for the purpose of certifying the ENERGY STAR product.

368 3.2.2 Power Supply Efficiency Criteria: Power Supplies used in products eligible under this specification
369 must meet the following requirements when tested using the *Generalized Internal Power Supply*
370 *Efficiency Test Protocol, Rev. 6.7* (available at www.efficientpowersupplies.org). Power Supply
371 data generated using Rev. 6.4.2 (as required in Version 1.1), 6.4.3, 6.5, or 6.6 are acceptable
372 provided the test was conducted prior to the effective date of Version 3.0 of this specification.

373 i. Pedestal and Rack-mounted Servers: To certify for ENERGY STAR, a pedestal or rack-
374 mounted computer server must be configured with **only** PSUs that meet or exceed the
375 applicable efficiency requirements specified in Table 1 **prior to shipment**.

376 ii. Blade and Multi-node Servers: To certify for ENERGY STAR, a Blade or Multi-node computer
377 server shipped with a chassis must be configured such that **all** PSUs supplying power to the
378 chassis meet or exceed the applicable efficiency requirements specified in Table 1 **prior to**
379 **shipment**.

380

Table 1: Efficiency Requirements for PSUs

Power Supply Type	Rated Output Power	10% Load	20% Load	50% Load	100% Load
Multi-output (Ac-Dc)	All Output Levels	N/A	90%	92%	89%
Single-output (Ac-Dc)	All Output Levels	83%	90%	94%	91%

381 3.2.3 Power Supply Power Factor Criteria: Power Supplies used in Computers Servers eligible under
 382 this specification must meet the following requirements when tested using the *Generalized*
 383 *Internal Power Supply Efficiency Test Protocol, Rev. 6.7* (available at
 384 www.efficientpowersupplies.org). Power Supply data generated using Rev. 6.4.2 (as required in
 385 Version 1.1), 6.4.3, 6.5 or 6.6 are acceptable provided the test was conducted prior to the
 386 effective date of Version 3.0.

- 387 i. Pedestal and Rack-mounted Servers: To certify for ENERGY STAR, a pedestal or rack-
 388 mounted computer server must be configured with **only** PSUs that meet or exceed the
 389 applicable power factor requirements specified in Table 2 **prior to shipment**, under all
 390 loading conditions for which output power is greater than or equal to 75 watts. Partners are
 391 required to measure and report PSU power factor under loading conditions of less than 75
 392 watts, though no minimum power factor requirements apply.
- 393 ii. Blade or Multi-node Servers: To certify for ENERGY STAR, a Blade or Multi-node computer
 394 server shipped with a chassis must be configured such that **all** PSUs supplying power to the
 395 chassis meet or exceed the applicable power factor requirements specified in Table 2 **prior**
 396 **to shipment**, under all loading conditions for which output power is greater than or equal to
 397 75 watts. Partners are required to measure and report PSU power factor under loading
 398 conditions of less than 75 watts, though no minimum power factor requirements apply.

399

Table 2: Power Factor Requirements for PSUs

Power Supply Type	Rated Output Power	10% Load	20% Load	50% Load	100% Load
Ac-Dc Multi-output	All Output Ratings	N/A	0.80	0.90	0.95
Ac-Dc Single-output	Output Rating ≤ 500 W	N/A	0.80	0.95	0.95
	Output Rating > 500 W and Output Rating ≤ 1,000 W	0.65	0.80	0.95	0.95
	Output Rating > 1,000 watts	0.80	0.90	0.95	0.95

400

401 **3.3 Power Management Requirements**

402 3.3.1 Server Processor Power Management: To certify for ENERGY STAR, a Computer Server must
 403 offer processor power management that is enabled by default in the BIOS and/or through a
 404 management controller, service processor, and/or the operating system shipped with the
 405 computer server. **All** processors must be able to reduce power consumption in times of low
 406 utilization by:

- 407 i. reducing voltage and/or frequency through Dynamic Voltage and Frequency Scaling (DVFS),
 408 or

- 409 ii. enabling processor or core reduced power states when a core or socket is not in use.
- 410 3.3.2 Supervisor Power Management: To certify for ENERGY STAR, a product which offers a pre-
- 411 installed supervisor system (e.g., operating system, hypervisor) must offer supervisor system
- 412 power management that is enabled by default.
- 413 3.3.3 Power Management Reporting: To certify for ENERGY STAR, all power management techniques
- 414 that are enabled by default must be detailed in the certification submission. This requirement
- 415 applies to power management features in the BIOS, operating system, or any other origin that
- 416 can be configured by the end-user.

417 **Note:** EPA has removed an outdated reference to the PPDS and clarified that power management

418 feature details are instead submitted through the ENERGY STAR Qualified Product Exchange (QPX)

419 system in the certification process.

420 3.4 Blade and Multi-Node System Criteria

- 421 3.4.1 Blade and Multi-Node Thermal Management and Monitoring: To certify for ENERGY STAR, a
- 422 blade or multi-node server must provide real-time chassis or blade/node inlet temperature
- 423 monitoring and fan speed management capability that is enabled by default.
- 424 3.4.2 Blade and Multi-Node Server Shipping Documentation: To certify for ENERGY STAR, a blade or
- 425 multi-node server that is shipped to a customer independent of the chassis must be accompanied
- 426 with documentation to inform the customer that the blade or multi-node server is ENERGY STAR
- 427 qualified only if it is installed in a chassis meeting requirements in *Section 3.4.1* of this document.
- 428 A list of certified chassis and ordering information must also be provided as part of product
- 429 collateral provided with the blade or multi-node server. These requirements may be met via either
- 430 printed materials, electronic documentation provided with the blade or multi-node server, or
- 431 information publicly available on the Partner's website where information about the blade or multi-
- 432 node server is found.

433 3.5 Active State Efficiency Criteria

- 434 3.5.1 Active State Efficiency Reporting: To certify for ENERGY STAR, a Computer Server or Computer
- 435 Server Product Family must be submitted for certification with the following information disclosed
- 436 in full and in the context of the complete Active State efficiency rating test report:
- 437 i. Final SERT rating tool results, which include the results files (in xml, html, and text format)
- 438 and all results-chart png files; and
- 439 ii. Intermediate SERT rating tool results over the entire test run, which include the results-details
- 440 files (in xml, html, and text format) and all results-details-chart png files.
- 441 Data reporting and formatting requirements are discussed in Section 4.1 of this specification.
- 442 3.5.2 Incomplete Reporting: Partners shall not selectively report individual workload module results, or
- 443 otherwise present efficiency rating tool results in any form other than a complete test report, in
- 444 customer documentation or marketing materials.
- 445 3.5.3 Active State Efficiency Requirements: Calculated Active State efficiency score (Eff_{ACTIVE}) shall be
- 446 greater than or equal to the minimum Active State efficiency thresholds listed in Table 3 for **all**
- 447 configurations submitted for certification within a product family, as well as any additional
- 448 configurations within the product family shipped as ENERGY STAR.

449 Equation 3: Calculation Eff_{ACTIVE}

$$450 \quad Eff_{ACTIVE} = EXP(0.65 * \ln(Eff_{CPU}) + 0.30 * \ln(Eff_{MEMORY}) + 0.05 * \ln(Eff_{STORAGE}))$$

451 *Where:*

- 452 ▪ Eff_{ACTIVE} is comprised of Eff_{CPU} , Eff_{MEMORY} and $Eff_{STORAGE}$
- 453 which are defined in equations 4 through 6 below:

454

Equation 4: Calculation Eff_{CPU}

455

$$Eff_{CPU} = Geomean(Eff_{COMPRESS}, Eff_{LU}, Eff_{SOR}, Eff_{CRYPTO}, Eff_{SORT}, Eff_{SHA256}, Eff_{HYBRIDSSJ})$$

456

Where:

457

- $Eff_{COMPRESS}$ is the calculated Compression worklet score

458

- Eff_{LU} is the calculated LU worklet score

459

- Eff_{SOR} is the calculated SOR worklet score

460

- Eff_{CRYPTO} is the calculated Crypto worklet score

461

- Eff_{SORT} is the calculated Sort worklet score

462

- Eff_{SHA256} is the calculated SHA256 worklet score

463

- $Eff_{HYBRIDSSJ}$ is the calculated Hybrid SSJ worklet score

464

465

Equation 5: Calculation Eff_{MEMORY}

466

$$Eff_{MEMORY} = Geomean(Eff_{FLOOD2}, Eff_{CAPACITY2})$$

467

Where:

468

- Eff_{FLOOD2} is the calculated Flood2 worklet score

469

- $Eff_{CAPACITY2}$ is the calculated Capacity2 worklet score

470

471

Equation 6: Calculation $Eff_{STORAGE}$

472

$$Eff_{STORAGE} = Geomean(Eff_{SEQUENTIAL}, Eff_{RANDOM})$$

473

Where:

474

- $Eff_{SEQUENTIAL}$ is the calculated Sequential worklet score

475

- Eff_{RANDOM} is the calculated Random worklet score

476

477

Equation 7: Calculation Eff_i

478

$$Eff_i = 1000 \frac{Perf_i}{Pwr_i}$$

479

Where:

480

- i = Represents each workload referenced in Equations 4 through 6

481

- $Perf_i$ = Geometric mean of the normalized interval performance measurements.

482

483

484

- Pwr_i = Geometric mean of the calculated interval power values.

485

486

487

Note: EPA has included a new equation above to clarify how to calculate individual worklet efficiency (Eff_i) scores which aligns with the guidance provided in SPEC SERT documentation. EPA has also clarified that Section 3.5.3 and the requirements in Table 3 below apply to all configurations shipped as ENERGY STAR.

488

489

490

Table 3: Active State Efficiency Thresholds for all Computer Servers

Product Type	Minimum <i>Eff_{ACTIVE}</i>
One Installed Processor	
Rack	11.0
Tower	9.4
Blade or Multi-Node	9.0
Resilient	4.8
Two Installed Processors	
Rack	13.0
Tower	12.0
Blade or Multi-Node	14.0
Resilient	5.2
Greater Than Two Installed Processors	
Rack	16.0
Blade or Multi-Node	9.6
Resilient	4.2

492

493 **Note:** While EPA received broad support for adding active state requirements, some stakeholders
494 requested changes to the levels proposed in Draft 3. Some stakeholders requested more stringent levels
495 across all categories. Other stakeholders commented that levels for some categories should be eased.
496 In particular, a stakeholder recommended that the active efficiency levels for greater than two installed
497 processor rack servers be eased from 16.0 to 13.0. EPA reviewed its dataset and analysis and
498 determined that the levels proposed for greater than two installed processor rack servers as well as all
499 other categories are well supported by the dataset. Further, EPA believes that with these levels
500 purchasers will have a good selection of ENERGY STAR products across all categories. As such, EPA
501 has maintained the Draft 3 levels.

502 3.6 Idle State Efficiency Criteria

503 3.6.1 **Idle State Data Reporting:** Idle State power (P_{IDLE} , P_{BLADE} , or P_{NODE}) shall be measured and
504 reported, both in certification materials and as required in Section 4 for all computer server types.
505 In addition, for blade and multi-node products, $P_{TOT_BLADE_SYS}$ and $P_{TOT_NODE_SYS}$ shall also be
506 reported respectively. Please see Section 3.7 for details on how to calculate P_{BLADE} and
507 $P_{TOT_BLADE_SYS}$, and Section 3.8 for details on how to calculate P_{NODE} and $P_{TOT_NODE_SYS}$.

508 3.7 Calculating Idle State Values – Blade Servers

509 3.7.1 The testing of Blade Servers for compliance with Section 3.6.1 shall be carried out under all of the
510 following conditions:

- 511 i. Power values shall be measured and reported using a half-populated Blade Chassis. Blade
512 Servers with multiple power domains, choose the number of power domains that is closest to
513 filling half of the Blade Chassis. In a case where there are two choices that are equally close
514 to half, test with the domain or combination of domains which utilize a higher number of Blade
515 Servers. The number of blades tested during the half-populated Blade Chassis test shall be
516 reported.

- 517 ii. Power for a fully-populated blade chassis may be optionally measured and reported, provided
 518 that half-populated chassis data is also provided.
- 519 iii. All Blade Servers installed in the Blade Chassis shall share the same configuration
 520 (homogeneous).
- 521 iv. Per-blade power values shall be calculated using Equation 8.

522 **Equation 8: Calculation of Single Blade Power**

523
$$P_{BLADE} = \frac{P_{TOT_BLADE_SYS}}{N_{INST_BLADE_SRV}}$$

524 *Where:*

- 526 ▪ *P_{BLADE} is the per-Blade Server Power, P_{TOT_BLADE_SYS} is total measured power of the Blade System,*
- 527
- 528 ▪ *N_{INST_BLADE_SRV} is the number of installed Blade Servers in the tested Blade Chassis.*
- 529
- 530

531 **3.8 Calculating Idle State Values – Multi-Node Servers**

532 3.8.1 The testing of Multi-Node Servers for compliance with Section 3.6.1 shall be carried out under all
 533 of the following conditions:

- 534 i. Power values shall be measured and reported using a fully-populated Multi-Node Chassis.
- 535 ii. All Multi-Node Servers in the Multi-Node Chassis shall share the same configuration
 536 (homogeneous).
- 537 iii. Per-node power values shall be calculated using Equation 9.

538 **Equation 9: Calculation of Single Node Power**

539
$$P_{NODE} = \frac{P_{TOT_NODE_SYS}}{N_{INST_NODE_SRV}}$$

540 *Where:*

- 541 ▪ *P_{NODE} is the per-Node Server Power, P_{TOT_NODE_SYS} is total measured power of the Multi-Node Server,*
- 542
- 543 ▪ *N_{INST_NODE_SRV} is the number of installed Multi-Node Servers in the tested Multi-Node Chassis.*
- 544

545 **3.9 Other Testing Criteria**

546 3.9.1 APA Requirements: For all computer servers sold with expansion APAs, the following criteria and
 547 provisions apply:

- 548 i. For all configurations, Active State and Idle State testing shall be conducted without any
 549 APAs installed which may be offered with the product. Where an APA relies on a separate
 550 PCIE switch for communication between the APA and CPU, the separate PCIE card(s) or
 551 riser(s) shall be removed for Active State and Idle State testing of all configurations.
- 552 ii. Manufacturers shall report the model name, model number, idle power consumption, and
 553 number of APA devices on each APA card for each APA offered as an accessory within an
 554 ENERGY STAR product family.
- 555 iii. The idle power for the expansion APA card shall be calculated by installing the APA
 556 expansion card in the computer server and performing just the SERT idle test (skipping the
 557 worklet tests) and subtracting the SERT idle power measured without the APA present in the
 558 computer servers.

559 iv. Where a removable switch is required to support the expansion APA, the switch should be
560 installed with the APA and included in the APA card idle measurement and calculation above.

561 **Note:** Based on stakeholder feedback, EPA has added guidance on how to measure APA card idle power
562 for certification purposes.

563 4 STANDARD INFORMATION REPORTING REQUIREMENTS

564 4.1 Data Reporting Requirements

565 4.1.1 All required data fields in the ENERGY STAR Version 3.0 Computer Servers Qualified Product
566 Exchange form shall be submitted to EPA for each ENERGY STAR certified Computer Server or
567 Computer Server Product Family.

568 i. Partners are encouraged to provide one set of data for each ENERGY STAR certified product
569 configuration, though EPA will also accept a data set for each qualified product family.

570 ii. A product family certification must include data for all defined test points in 1.G)2), as
571 applicable.

572 iii. Whenever possible, Partners must also provide a hyperlink to a detailed power calculator on
573 their Web site that purchasers can use to understand power and performance data for
574 specific configurations within the product family.

575 4.1.2 The following data will be displayed on the ENERGY STAR Web site through the product finder
576 tool:

577 i. model name and number, identifying SKU and/or configuration ID;

578 ii. system characteristics (form factor, available sockets/slots, power specifications, etc.);

579 iii. system type (e.g. resilient.);

580 iv. system configuration(s) (including Low-end Performance Configuration, High-end
581 Performance Configuration, and Typical Configuration for Product Family certification);

582 v. power consumption and performance data from required Active and Idle State Efficiency
583 Criteria testing including results.xml, results.html, results.txt, all results-chart png files,
584 results-details.html, results-details.txt, results-details.xml, all results-details-chart png files;

585 vi. available and enabled power saving features (e.g., power management);

586 vii. a list of selected data from the ASHRAE Thermal Report;

587 viii. inlet air temperature measurements made prior to the start of testing, at the conclusion of Idle
588 State testing, and at the conclusion of Active State testing;

589 ix. for product family certifications, a list of qualified configurations with qualified SKUs or
590 configuration IDs; and

591 x. for a blade server, a list of compatible blade chassis that meet ENERGY STAR certification
592 criteria.

593 4.1.3 EPA may periodically revise this list, as necessary, and will notify and invite stakeholder
594 engagement in such a revision process.

595 **5 STANDARD PERFORMANCE DATA MEASUREMENT AND OUTPUT**
596 **REQUIREMENTS**

597 **5.1 Measurement and Output**

598 5.1.1 A computer server must provide data on input power consumption (W), inlet air temperature (°C),
599 and average utilization of all logical CPUs. Data must be made available in a published or user-
600 accessible format that is readable by third-party, non-proprietary management software over a
601 standard network. For blade and multi-node servers and systems, data may be aggregated at the
602 chassis level.

603 5.1.2 Computer servers classified as Class B equipment as set out in EN 55022:2006 are exempt from
604 the requirements to provide data on input power consumption and inlet air temperature in 5.1.1.
605 Class B refers to household and home office equipment (intended for use in the domestic
606 environment). All computer servers in the program must meet the requirement and conditions to
607 report utilization of all logical CPUs.

608 **5.2 Reporting Implementation**

609 5.2.1 Products may use either embedded components or add-in devices that are packaged with the
610 computer server to make data available to end users (e.g., a service processor, embedded power
611 or thermal meter (or other out-of-band technology), or pre-installed OS);

612 5.2.2 Products that include a pre-installed OS must include all necessary drivers and software for end
613 users to access standardized data as specified in this document. Products that do not include a
614 pre-installed OS must be packaged with printed documentation of how to access registers that
615 contain relevant sensor information. This requirement may be met via either printed materials,
616 electronic documentation provided with the computer server, or information publicly available on
617 the Partner's website where information about the computer server is found.

618 5.2.3 When an open and universally available data collection and reporting standard becomes
619 available, manufacturers should incorporate the universal standard into their systems;

620 5.2.4 Evaluation of the accuracy (5.3) and sampling (5.4) requirements shall be completed through
621 review of data from component product datasheets. If this data is absent, Partner declaration
622 shall be used to evaluate accuracy and sampling.

623 **5.3 Measurement Accuracy**

624 5.3.1 *Input power:* Measurements must be reported with accuracy of at least $\pm 5\%$ of the actual value,
625 with a maximum level of accuracy of $\pm 10W$ for each installed PSU (i.e., power reporting accuracy
626 for each power supply is never required to be better than ± 10 watts) through the operating range
627 from Idle to full power;

628 5.3.2 *Processor utilization:* Average utilization must be estimated for each logical CPU that is visible to
629 the OS and must be reported to the operator or user of the computer server through the operating
630 environment (OS or hypervisor);

631 5.3.3 *Inlet air temperature:* Measurements must be reported with an accuracy of at least $\pm 2^\circ C$.

632 **5.4 Sampling Requirements**

633 5.4.1 *Input power and processor utilization:* Input power and processor utilization measurements must
634 be sampled internally to the computer server at a rate of greater than or equal to measurement
635 per contiguous 10 second period. A rolling average, encompassing a period of no more than 30
636 seconds, must be sampled internally to the computer server at a frequency of greater than or
637 equal to once per ten seconds.

638 5.4.2 *Inlet air temperature:* Inlet air temperature measurements must be sampled internally to the
639 computer server at a rate of greater than or equal to 1 measurement every 10 seconds.

640 5.4.3 *Time stamping*: Systems that implement time stamping of environmental data shall sample
641 internally to the computer server data at a rate of greater than or equal to 1 measurement every
642 30 seconds.

643 5.4.4 *Management Software*: All sampled measurements shall be made available to external
644 management software either via an on-demand pull method, or via a coordinated push
645 method. In either case the system's management software is responsible for establishing the
646 data delivery time scale while the computer server is responsible to assuring data delivered
647 meets the above sampling and currency requirements.

648 6 TESTING

649 6.1 Test Methods

650 6.1.1 When testing Computer Server products, the test methods identified in 6 shall be used to
651 determine ENERGY STAR certification.

652 **Table 6: Test Methods for ENERGY STAR Certification**

Product Type or Component	Test Method
All	ENERGY STAR Test Method for Computer Servers (Rev. July-2018)
All	Standard Performance Evaluation Corporation (SPEC) most current ⁴ Server Efficiency Rating Tool (SERT)

653 6.1.2 When testing Computer Server products, UUTs must have the maximum number of Processor
654 Sockets populated to represent that product family during testing. All systems will be subject to
655 active efficiency threshold requirements based on the number of sockets populated in the system
656 during testing.

657 **Note:** EPA has revised Section 6.1.2 to reflect the changes to the product family definition above. All
658 configurations within a product family shall be populated to the maximum socket population count that
659 represents that particularly product family, and must meet the applicable active efficiency threshold for the
660 number of sockets populated, **not** the number of sockets on the motherboard.

661 6.2 Number of Units Required for Testing

662 6.2.1 Representative Models shall be selected for testing per the following requirements:

663 i. For certification of an individual product configuration, the unique configuration that is
664 intended to be marketed and labeled as ENERGY STAR is considered the Representative
665 Model.

666 ii. For certification of a product family of all product types, one product configuration for each
667 of the three points identified in definitions 1.G)2) within the family are considered
668 Representative Models. All such representative models shall have the same Common
669 Product Family Attributes as defined in 1.G)1).

670 6.2.2 All product configurations within a product family that is submitted for certification must meet
671 ENERGY STAR requirements, including products for which data is not reported.

⁴ For the purposes of this document, the most current SERT version will be listed in the most recently published Servers 3.0 Clarification Memo, located on the Enterprise Servers Specification Version 3.0 website (https://www.energystar.gov/products/spec/enterprise_servers_specification_version_3_0_pd)

672 **7 EFFECTIVE DATE**

673 7.1.1 Effective Date: This ENERGY STAR Computer Servers specification shall take effect on **May 10,**
674 **2019**. To certify for ENERGY STAR, a product model shall meet the ENERGY STAR
675 specification in effect on its date of manufacture. The date of manufacture is specific to each unit
676 and is the date on which a unit is considered to be completely assembled.

677 7.1.2 Future Specification Revisions: EPA reserves the right to change this specification should
678 technological and/or market changes affect its usefulness to consumers, industry, or the
679 environment. In keeping with current policy, revisions to the specification are arrived at through
680 stakeholder discussions. In the event of a specification revision, please note that the ENERGY
681 STAR certification is not automatically granted for the life of a product model.

682 **8 CONSIDERATIONS FOR FUTURE REVISIONS**

683 **8.1 TBD**